



Material Safety Data Sheet

1.0 Product and Company Identification

Identification of the preparation: **C6578 Series – No 78 Color**

Use of the preparation: Inkjet printing

Company Identification: Hewlett-Packard Company
1000 NE Circle Boulevard
Corvallis, Oregon 97330-4239
United States

Emergency telephone number 1-800-457-4209 (USA and Canada)
Hewlett-Packard Health Effects Line: 503-494-7199 (USA direct)
Singapore: +001-800-332-13321

General information telephone number: 208-323-2551 (USA direct)

Local Contact Information

Ireland
Liffey Park Technology Campus
Barnhall Road,
Leixlip, Co. Kildare
Phone: 01 6150000

United Kingdom
Hewlett-Packard, Ltd.
Cain Road, Amen Corner
Bracknell, Berkshire, RG12 1HN
Phone: 1344 36-0000

Hazard Rating	NFPA/HMIS
Health	1
Flammability	1
Instability/Reactivity	0
Special	none

2.0 Composition/Information on Hazardous Ingredients

This ink supply contains an aqueous ink formulation

For cyan (blue) ink only:

Component/Substance	CAS Number	EU Number	% by Weight	EU classification
Ethyl alkylidol	confidential	confidential	<10	not classified
2-Pyrrolidone	616-45-5	210-843-1	<8	Xi; R36/37/38
Ammonium nitrate	6484-52-2	229-347-8	<3	O; Xi; R8-36/37/38
Metal nitrate	confidential	confidential	<8	O; Xi; R8-36/37/38
1,5-Pentanediol	111-29-5	203-854-4	<10	not classified
Alkylidol ethoxylate #1	confidential	confidential	<3	Xi; R38-41
Alkylidol ethoxylate #2	confidential	confidential	<3	Xi; R36/38



Material Safety Data Sheet

Substituted phthalocyanine salt	confidential	confidential	<4	Xn; N; R22- 48/22- 51/53
Water	7732-18-5	231-791-2	>50	not classified

For magenta (red) ink only:

Component/Substance	CAS Number	EU Number	% by Weight	EU classification
Ethyl alkyl diol	confidential	confidential	<10	not classified
2-Pyrrolidone	616-45-5	210-843-1	<8	Xi; R36/37/38
Ammonium nitrate	6484-52-2	229-347-8	<3	O; Xi; R8-36/37/38
Metal nitrate	confidential	confidential	<8	O; Xi; R8-36/37/38
1,5-Pentanediol	111-29-5	203-854-4	<10	not classified
Alkyl diol ethoxylate #1	confidential	confidential	<3	Xi; R38-41
Alkyl diol ethoxylate #2	confidential	confidential	<3	Xi; R36/38
Amino alkyl diol	confidential	confidential	<3	Xi; R36/37/38
Water	7732-18-5	231-791-2	>50	not classified

For yellow ink only:

Component/Substance	CAS Number	EU Number	% by Weight	EU classification
Ethyl alkyl diol	confidential	confidential	<10	not classified
2-Pyrrolidone	616-45-5	210-843-1	<8	Xi; R36/37/38
Ammonium nitrate	6484-52-2	229-347-8	<3	O; Xi; R8-36/37/38
Metal nitrate	confidential	confidential	<8	O; Xi; R8-36/37/38
1,5-Pentanediol	111-29-5	203-854-4	<10	not classified
Alkyl diol ethoxylate #1	confidential	confidential	<3	Xi; R38-41
Alkyl diol ethoxylate #2	confidential	confidential	<3	Xi; R36/38
Water	7732-18-5	231-791-2	>50	not classified

3.0 Hazard Identification

The cyan ink is classified for environmental effects according to EU Directive 1999/45/EC with R52-53. The magenta and yellow inks are not classified according to EU Directive 1999/45/EC

3.1 Routes of Exposure Potential routes of overexposure to this product are skin and eye contact.

Inhalation of vapor and ingestion are not expected to be significant routes of exposure for this product under normal use conditions.

Complete toxicity data are not available for this specific formulation.

3.2 Acute Health Hazards

Any potential hazards are presumed to be due to exposure to the components.

Ethyl alkyl diol: Contact with eyes and skin may cause mild



Material Safety Data Sheet

irritation.

2-Pyrrolidone: Contact with eyes and skin may result in irritation. Inhalation may result in respiratory irritation. Ingestion may result in nausea, vomiting, and diarrhea.

Ammonium nitrate and metal nitrate: Contact with eyes and skin may cause irritation. Inhalation may cause respiratory irritation.

Note: Nitrates and their derivatives can cause methemoglobinemia and result in respiratory depression. Primary indicators of prolonged exposure include shortness of breath, headaches, dizziness and cyanosis (bluish skin and lips).

1,5-Pentanediol: Contact with eyes and skin may cause irritation.

Alkyldiol ethoxylate #1: Contact with eyes may result in severe irritation and corneal injury. Contact with skin may result in severe irritation. Ingestion may cause irritation of mouth and throat, nausea, vomiting and diarrhea.

Alkyldiol ethoxylate #2: Contact with eyes and skin may result in severe irritation. Ingestion may cause irritation of mouth, throat, nausea, vomiting, and diarrhea.

Cyan Ink Only:

Substituted phthalocyanine salt: Harmful if swallowed.

Magenta Ink Only:

Amino Alkyldiol: Contact with eyes and skin may result in irritation. Inhalation may result in respiratory irritation.

3.3 Chronic Health Hazards

3.4 Carcinogenicity

Cyan Ink Only:

Substituted phthalocyanine salt: Prolonged ingestion exposure may result in serious damage to health.

None of the components present in this formulation at concentrations equal to or greater than 0.1% are listed by EU, MAK, IARC, NTP or OSHA.

4.0 First Aid Measures

Emergency telephone number
Hewlett-Packard Health Effects
Line:

1-800-457-4209 (USA and Canada)
503-494-7199 (USA direct)
Singapore: +001-800-332-13321

Inhalation:

Remove to fresh air. If symptoms persist, consult a physician.

Ingestion:

If stomach upset persists, consult a physician.

Skin:

Wash affected areas thoroughly with soap and water. If irritation persists, consult a physician.



Material Safety Data Sheet

Eyes: Do not rub eyes. Immediately flush with large amounts of clean, lukewarm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists, consult a physician.

5.0 Fire Fighting Measures

Extinguishing media: Water, dry chemical, carbon dioxide, foam
Unsuitable Extinguishing Media: None known
Special Firefighting Procedures: None known
Unusual fire and explosion hazards: No special hazards known
Auto-ignition temperature: Not determined
Flashpoint (method): > 200° F, > 93.3° C (US EPA Method 1020)
Hazardous Combustion Products Refer to section 10.

6.0 Accidental release measures

Spill or Leak Procedures: Standard eye and skin protection is recommended.
Environmental precautions: Do not discharge into drains (See also Section 13, Disposal considerations)

7.0 Handling and Storage

Storage Temperature: 59° F to 95° F; 15° C to 35° C
Handling and Storage precautions: Keep out of the reach of children
Keep away from extreme heat or cold.
Shelf Life: 1 year
Special Sensitivity: None

8.0 Exposure control/ personal protection

8.1 Exposure Limit Values None established.
8.2 Exposure Controls Standard eye and skin protection for laboratory chemical safety is recommended. Use in well ventilated area.



Material Safety Data Sheet

9.0 Physical and chemical properties

pH:	6.6 – 8.5
Boiling point:	Not Determined
Flash point:	> 200° F, > 93.3° C
Flammability:	US NFPA/HMIS Flammability rating = 1
Explosive properties:	Not applicable
Oxidizing properties:	Not applicable
Vapor Pressure:	Not applicable
Relative density:	Specific Gravity 1.0 to 1.2
Solubility:	Soluble in water
Partition coefficient:	Not determined
Viscosity:	Not determined
Vapor density:	>1 (air = 1.0)
Evaporation rate:	Not applicable
Other:	Not applicable

10.0 Stability and reactivity

Stability:	Stable under normal storage conditions
Incompatibilities:	Strong oxidizers, strong gases, bleach and other hypo-chlorite containing cleaning agents
Thermal decomposition products:	Oxides of carbon/nitrogen/sulfur; water
Hazardous polymerization:	None

11.0 Toxicological information

Refer to Section 3 for potential health effects and Section 4 for first aid measures
Ink formulations have not been tested.

12.0 Ecological information

Cyan, Magenta, Yellow Inks:

96 Hour LC50	LC50 < 400mg/L	Fathead minnow
96 Hour LC50	Survival (100mg/L) = 100%	Trout
	Survival (10mg/L) = 100%	

13.0 Disposal considerations

Dispose in accordance with all applicable US Federal, state, local, and country laws.

14.0 Transportation information

Not a regulated article under United States DOT, IATA, ADR, or RID.



Material Safety Data Sheet

UN Number:	Not applicable
Class:	Not applicable
Proper Shipping Name:	Not applicable
Packing Group:	Not applicable
Marine Pollutant:	Not listed
Special Precautions:	None noted

15.0 Regulatory information

US EPA TSCA Inventory:	All ingredients are listed or exempt.
US EPA TSCA 12(b):	Does not contain listed chemicals.
EU Notification:	All ingredients are listed on EINECS and/or ELINCS or exempt.
EU Hazard Label (1999/45/EC):	Product may require a label according to EU Directive 1999/45/EC

16.0 Other information

Date Prepared:	June 29, 2002
HP-DMS Document Control Number:	09000de78022847b-eng
Revision Information:	This document replaces all prior versions of the MSDS
EU Risk (R) Phrase definitions:	R8: Contact with combustible material may cause fire R22: Harmful if swallowed R38: Irritating to skin R41: Possible risks of irreversible effects R36/38: Irritating to eyes and skin R48/22: Harmful: danger of serious damage to health by prolonged exposure if swallowed R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment R36/37/38: Irritating to eyes, respiratory system and skin.
Other Information:	This MSDS was prepared in compliance with EU Directive 91/155/EEC as amended by 2001/58/EC and USA OSHA Hazard Communications regulations (29CFR1910:1200).

DISCLAIMER: This Material Safety Data Sheet (MSDS) is provided without charge to customers of Hewlett-Packard. Data is the most current known to Hewlett-Packard at the time of preparation of this MSDS and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application.